22 Group TempScan

Dan Mitchell - dan@22groupconsulting.com - 269.370.8920

WILL YOUR BUSINESS SURVIVE COVID-19?

A Small investment in safety goes a long way.

- Keep your employees safe
- Keep your customers safe
- Temperature detection in less than 1 second
- 8" IPS full view LCD dsplay
- Water & dust resistant

Wouldn't you feel safer somewhere you knew nobody had a fever? Your customers will.



FACTORY

staff are fit to

work before

starting their

shift



employees are fit

and safe to work



entering their

HR

place of

employment

Checking all staff

HOSPITALS Entry to buildings or ICU areas

GYMS



Confirming all VENUES Checking customers are safe and well to socialise

ENTERTAINMENT Checking users

on entry assuring guest safety

children are safe to attend school

PLUG & PLAY FUNCTIONALIT Designed for ease of use & simplistic integration into your business. No professional setup is required, no calibration needed.

FEATURES

- Install as a wall a mounted device, on our podium, counter top mount, or easily integrate into a turnstile/gate or tabletop using the post mount.
- Temperature is taken almost instantly, with or without an audible alarm for over temp, or a simple LED notification.



 Integrate with time clocks or place near employee entrances to protect personnel.







COUNTER TOP



- Optional facial recognition in less than one second.
- Ability to store up to 30,000 faces.
- Automatic notification of abnormal body temperature.
- Temperature measurement data exported in real time.
- Infared thermal imaging for face-with-mask identity.



269.370.8920

www.22groupconsulting.com

SPECIFICATIONS

Product	FaceScan 1000	Interface	Ethernet and WIFI	PC	RK3288 quad-core	Operating Temp	0°C - 60°C	
Screen size	8" - 800*1280		2.5W / 4R Speakers		EMMC 8GB	Storage Temp	-20°C - 60°C	
LCD Type	IPS LCD screen	1	x USB OTG, 1 x USB Host	Thermal Imaging	1 meter	Installation Wall	/ Gate Bracket	
Camera Binocular Wide Dynamic			RS232 Serial Port	10°C ~ 42°C S		i ize (std) 274 x 128 x 21.5 (mm)		
Cam resolution	2-million pixels	Wiegard	Wiegard 26/34 output and input		Accuracy≤±0.5°C	Size (IC Card) 298 x 132 x 25 (mm)		
Aperture	F2.4		Support Uboot upgrade	Power	DC12V (±10%)	Packing	Machine	
Lighting LED and IR	Dual Photo Flood	1	door open Relay Output		13.5W (Max)	1 x Power ada	ptor, 1 x Manual	
Accessories				· · ·				
Wall Brackets	Simple design, standard fixings				Alert Lamp 3rd Party view of entry decisio		of entry decision	
Podium	Floor mount	ed, power nee	ded through base					
Features								
Face Recognition	Up to 30,000 stored faces			Identity Distance Configuration		included		
Face Comparison	Mask Advisory message			Unit Configuration		Secure local access		
Stranger Detection	compatible	compatible with Face Recognition						
Notes								
Note	Installation I	oy others, Loca	I Software supply only in	English (UK). Any	cloud software will n	need to be created b	y end user.	
	External Sof	tware not requ	ired for operation. Stand	d alone installation	is fine.			
Warranty	1 year stand	ard warranty						
Delivery Time	2 weeks star	2 weeks standard						
Terms of Payment	100% on ord							
		k 128m	m					



Product of England Offered by 22 Group

269.370.8920